

## Langley Scissor Lift License

Langley Scissor Lift License - There is an inherent chance in operating a scissor lift, because with all kinds and types of powered work tools would require proper handling to be able to prevent accidents which can cause injuries or damage. Companies must ensure that staff utilizing this machinery have the necessary qualifications.

Companies must not allow scissor lifts to be utilized by unqualified people. The scissor lift is used to lift people to high levels. Failure to know and fully abide by safety standard could cause injuries for the users or damage to the lift.

For those who use scissor lifts, there is no legislation governing the use of fall protection. Nevertheless, manufacturers may recommend the use of fall protection and in several circumstances tying off in scissor lifts may be required by employer guidelines, local regulations or job-specific risk assessment.

To ensure that the scissor lift is in good working condition prior to using the machine, the operator has to carry out a thorough inspection. This is the operator's task, even though the unit has already been in service that day. The operator's handbook of the machinery contains a pre-operation checklist.

The things that an operator must look for when performing a scissor lift check, consists of checking tire-inflation pressure, and checking platform controls and ground controls to make sure they are working. Watch for any delayed movement on the fly section when the boom is retracting and extending because this can indicate some loose cables. While operating the controls, make certain that the emergency stop switches are working. Operate functions against the machine's cutout switches. Check the boom control system by cycling a boom lift to the furthest extent of its operating envelope. Safety limiters should automatically stop the unit before it moves into an unstable position, if they are working properly. If they aren't, turn off the lift and make sure that it is fixed before utilizing it for a second time.

Safe operating procedures must be followed at all time, with the levers being operated with even, controlled pressure. A control lever should never be pushed from one position to the opposite position. The lever should be shifted to neutral, before stopping, and afterward proceeding in the desired direction. When released, control switches and levers must automatically return to the neutral position. Depress the foot switch prior to operating platform controls.